


Item no.: 231-316/026-000
Product description: FEMALE PLUG; 16 POLE; PIN SPACING 5.08 MM / 0.2 IN;
WITH INTEGRATED FIXING FLANGES; CAGE
CLAMP®CONNECTION; WITH CODIG FINGERS



Packing unit 25 pieces

Product group	3 (Multi Conn. System)
Pin spacing from	5,08 mm
Pin spacing from	0,2 in
pole count	16
Cross section from [mm²]	0,08 mm²
Cross section to [mm²]	2,5 mm²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Weight	29,4 g
Color	orange
No. of connection Points	16
No. of potentials	16
Height	14,3 mm
Height	0,563 in
Width	82,78 mm
Width	3,259 in
Depth	26,45 mm



Depth	1,041 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
231-316/026-000	BV	11915/A0	400	16	2,5
231-316/026-000	CCA	5764	250	16	0,08-2,5
231-316/026-000	CSA	154112-1466354	300	15	22-12
231-316/026-000	DEMKO	88126	250		2,5
231-316/026-000	KEMA	2083746.02	250	16	0,08-2,5
231-316/026-000	KR	HMB05880-EL003	250/400/600	12/16	2,5
231-316/026-000	NEMKO	P94101840	250		2,5
231-316/026-000	UR	E45171	600	15	12
231-316/026-000	UR	E45172	300	15	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected