


Item no.: 231-608
Product description: MALE CONNECTOR; 8 POLE; PIN SPACING 5 MM / 0.197 IN;
CAGE CLAMP[®]CONNECTION



Packing unit 50 pieces

Product group	3 (Multi Conn. System)
Pin spacing from	5 mm
Pin spacing from	0,197 in
pole count	8
Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	2,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP [®] CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	12 A
Weight	11,926 g
Color	grey
No. of connection Points	8
No. of potentials	8
Height	14,3 mm
Height	0,563 in
Width	43,2 mm
Width	1,701 in
Depth	27,5 mm



Depth	1,083 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
231-608	BV	11915/A0	400	16	2,5
231-608	CCA	5764	250	12	0,08-2,5
231-608	CSA	154112-1466354	300	15	22-12
231-608	DEMKO	88126	250		2,5
231-608	KEMA	2083746.02	250	12	0,08-2,5
231-608	KR	HMB05880-EL003	250/400	12/16	2,5
231-608	NEMKO	P94101840	250		2,5
231-608	UR	E45171	600	15	12
231-608	UR	E45172	300	15	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected